B6200 MONO PRINTERS

- **B6200**
- **B6200n**
- **B6200dn**

FAST, VERSATILE, RELIABLE, PRODUCTIVE

The ultimate high speed, hardworking A4 mono printer that satisfies the needs of the most demanding small workgroups. With a class-leading combination of high standard memory and fast processing power, the B6200 prints quickly and offers two input trays as standard. Its high resolution ensures pin-sharp output every time- a must for all customer-facing documents. Productivity enhancing features abound: including PCL and PostScript compatibility for printing of graphic files such as PDFs and Mac files; flexible paper input options, additional paper trays for large capacity storage of multiple paper types and the optional envelope feeder that speeds up mailshots or mail merges. Feature rich, the B6200 is also fully networkable by means of a user-installable network card.

MAIN FEATURES OF THE B6200

- 24 pages per minute - print speed for demanding workgroups
- True 1200 dpi resolution for professional output
- 128MB standard memory ensures the printer can handle any job
- 266MHz Processor ensures shortest processing times
- Up to 1,500 sheets input for long print runs and less user intervention
- Genuine Adobe PostScript® 3
- Robust 75,000 pages per month maximum duty cycle

The B6200 is engineered specifically for professionals sharing print facilities.

OKI

B6200 MONO PRINTERS

PRODUCT SPECIFICATION

		B6200	B6200N	B6200DN
Order number		09004082	09004083	01147801
Speed & throughput	Print speed	24ppm		
	Time to first print	10.2 seconds		
	Warm up time	12 seconds	18 seconds	
	Processor speed	266MHz		
Print quality	Resolution	1200 x 1200 dpi		
Typefaces	PCL Printer fonts	90 scaleable fonts, 4 bitmap fonts		
	Barcode fonts	5 barcode fonts		
	PostScript fonts	136 fonts		
Compatibility	Printer languages	PCL5e, PCL6, Postscript3, Epson FX		
	OS Compatibility	Windows 95 / 98 / 98 SE / ME, Windows NT4 Workstation / NT4 Server / 2000 Workstation / 2000 Professional/ 2000 Server / 2000 Advanced Server / XP Professional / XP Home / NT Terminal Server Edition/ 2000 Terminal Server with Citrix Metaframe 1.8 or Citrix Metaframe XP 1.0. Mac OS 8.6 (or higher), Mac OS X (10.1 or higher), Variants of Unix and Linux via PPDs		
	Standard interfaces	IEEE1284 Bi–directional parallel, USB 2.0, 25 Pin RS232C serial	IEEE1284 Bi–directional parallel, USB 2.0, 10/100BaseTX Ethernet, 25 Pin RS232C serial	
	Optional interface	10/100BaseTX Ethernet	N/A	
	Network & protocols	10/100BaseTX Ethernet card with internal web server for printer and network card set-up and management. Includes POP3 and SMTP mail client for submission of print jobs and for alerts. All major network protocols supported - TCP/IP, Netware, Ethertalk and NetBEUI. TCP/IP :-ARP, RARP, IP, ICMP, TCP, DDP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMP, DNS, JetDirect protocols. Netware 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:– PServer, RPrinter, EtherTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP . NetBEUI:– SMB, NetBIOS		
	Utilities	Oki PrintSuperVision web based printer management software for Oki and other brand printers. Easy setup utility, Oki LPR utiilty, plug-ins for 3rd party management utilities		
Memory	Standard/Maximum	128/640MB		
	Flash memory	64, 128, 256mb Flash memory option for storage of fonts, forms and macros		
Paper handling	Internal tray capacity	400sheets (1st tray x 150, 2nd tray x 250), 60—216gsm (16—80lb)		
	Supported media sizes	A5, B5(JIS), A4, Exective, Letter, Legal13, Legal14, Custom size (98x148 - 216x356mm)		
	Manual feeder	N/A		
	Manual feeder capacity	N/A		
	Optional paper input trays	3rd/4th tray: 550sheets, 60—216gsm (16 — 80lb)		
	Output capacity	250 sheets face down		
	Duplex capability	Optional		Standard
	Duplex paper sizes	A5, A4, B5, Letter, Legal 13, Legal 14, Executive		
Operating conditions	Temperature/humidity (operating)	5C – 35C (41 - 95F), 15–85% RH non–condensing		
	Storage	0C – 35C (32 - 95F), 15–80% RH non–condensing		
Power requirements	Power supply	230 VAC +/- 10%, 50 or 60Hz +/- 2%		
	Power consumption	Deep sleep - 8W; Sleep - 14W; Idle - 97W; Operating (max.) - 1080W		
Physical	Noise	50.3dB(A)		
	Size (HxW x D)	324 x 422 x 455mm		
	Weight	Approx. 18.8kg		
	Monthly duty cycle (max.)	75,000 pages		
Warranty	Standard	One year on-site		
Supplies	Print Cartridge	10,000 pages @ 5% coverage		

OKI

Only use genuine Oki Original consumables to ensure the best quality and performance from your hardware. Non Oki Original products may damage your printer's performance and invalidate your warranty. Specifications subject to change without notice. All trademarks acknowledged.

Oki, Network Solutions for a Global Society

Oki Europe, Part of Oki Electric

Oki Europe Ltd,
Central House, Balfour Road,
Hounslow, Middlesex, TW3 1HY,
United Kingdom
tel: +44 (0)20 8219 2190
fax: +44 (0)20 8219 2199
www.okieurope.com

As an ENERGY STAR Partner, Oki Europe Ltd has determined that this product meets the ENERGY STAR guidelines for energy efficiency

2005
OKI
EUROPEAN CHALLENGE

Oki is proud to sponsor the Oki European Challenge - 2005. For more information visit **www.okieurochallenge.com**

©2004 Oki Europe Ltd.